



KALSI CENTRIFUGAL MONOBLOCK PUMPS

PERFORMANCE AT 220V, 3000 RPM, 50 Hz, SINGLE PHASE, AC SUPPLY



SrNo	HP / kW	MODEL	SYN. RPM	PUMP SIZE (mm)	Capacity	9 M	12 M	15 M	18 M	21 M	24 M	27 M	30 M	33 M	36 M	39 M	42 M	DUTY POINT
1.	2.0 / 1.5	CENTRIFUGAL	3000	50 x 50	LPM	450	420	380	320	-	-	-	-	-	-	-	-	21 m
2.	2.0 / 1.5	CENTRIFUGAL	3000	65 x 50	LPM	540	450	390	330	-	-	-	-	-	-	-	-	15 m
3.	2.0 / 1.5	CENTRIFUGAL	3000	80 x 80	LPM	720	480	-	-	-	-	-	-	-	-	-	-	10 m
4.	3.0 / 2.2	CENTRIFUGAL	3000	65 x 50	LPM	-	480	435	400	360	-	-	-	-	-	-	-	20 m
5.	3.0 / 2.2	CENTRIFUGAL	3000	80 x 80	LPM	900	800	560	-	-	-	-	-	-	-	-	-	13 m
6.	5.0 / 3.7	CENTRIFUGAL	3000	65 x 50	LPM	-	-	428	408	396	390	372	360	330	300	-	-	30 m
7.	5.0 / 3.7	CENTRIFUGAL	3000	80 x 80	LPM	-	840	780	720	660	540	360	-	-	-	-	-	21 m

THESE PUMPS ARE ALSO AVAILABLE IN THREE – PHASE , 415 VOLTS , 50 HZ , AC SUPPLY

Statutory Disclaimer:- In view of continual development, the performance figures / information / description / illustrations are subject to change without any prior notice. The performance data given is based on results achieved during tests conducted under ideal test conditions in a laboratory. Actual site conditions may result in variation in these performance values. Depending upon customer feedback and continual improvement, new models are introduced on regular basis, kindly consult your local dealer/re-seller for appropriate pump selection.

Total Head=Suction Head + Delivery Head + Friction Losses