



KALSI CENTRIFUGAL MONOBLOCK PUMPS

AS PER IS: 9079

PERFORMANCE CHARACTERISTICS OF HIGH HEAD, HIGH SPEED SUPER POWER MONOBLOCK PUMPS
THREE PHASE, 415 V, 3000 RPM, 50 Hz, A.C. SUPPLY, INSULATION CLASS 'A'



HP	kW	Size (mm)	RPM	Capacity	12 M	16 M	20 M	24 M	27 M	28 M	32 M	36 M	38 M	40 M	44 M	48 M	50 M	52 M	54 M	56 M	FL CURRENT	ISI MARK
3.0	2.2	65 x 50	2820	LPM	770	660	540	420	300	250	--	--	--	--	--	--	--	--	--	--	5.3 A	
5.0	3.7	65 x 50	2820	LPM	680	665	640	564	480	420	320	--	--	--	--	--	--	--	--	--	8.4 A	
7.5	5.5	65 x 50	2820	LPM	840	800	785	760	750	740	670	605	510	480	335	--	--	--	--	--	11.9 A	
10.0	7.5	50 x 40	2820	LPM	580	570	560	555	550	545	530	520	515	510	495	480	472	460	450	440	16.0 A	
10.0	7.5	65 x 50	2820	LPM	710	700	690	685	670	665	655	645	640	630	620	600	564	500	420	360	16.0 A	

Statutory Disclaimer:- In view of continual development, the performance figures / information / description / illustrations are subject to change without any prior notice. The performance data given is based on results achieved during tests conducted under ideal test conditions in a laboratory. Actual site conditions may result in variation in these performance values. Depending upon customer feedback and continual improvement, new models are introduced on regular basis, kindly consult your local dealer/re-seller for appropriate pump selection.

Total Head=Suction Head + Delivery Head + Friction Losses