



## KALSI CENTRIFUGAL MONOBLOCK PUMPS

AS PER IS: 9079

**PERFORMANCE CHARACTERISTICS OF SUPER POWER MONOBLOCK PUMPS  
THREE PHASE, 415 V, 3000 RPM, 50 Hz, A.C. SUPPLY, INSULATION CLASS 'B'**

HP	kW	Size (mm)	RPM	Capacity	10 M	15 M	20 M	22 M	25 M	30M	35 M	40 M	45 M	47 M	50 M	52 M	55 M	60 M	65 M	FL CURRENT	ISI MARK
3.0	2.2	65 x 50	2820	LPM	540	470	375	330	240	--	--	--	--	--	--	--	--	--	--	4.0	
5.0	3.7	65 x 50	2880	LPM	520	510	495	480	470	420	330	--	--	--	--	--	--	--	--	5.3	
7.5	5.5	65 x 50	2880	LPM	580	550	540	530	525	500	480	450	390	360	300	270	--	--	--	5.3	
10.0	7.5	65 x 50	2880	LPM	530	520	510	505	500	490	480	470	460	455	450	435	420	360	300	5.3	

**Statutory Disclaimer:-** In view of continual development, the performance figures / information / description / illustrations are subject to change without any prior notice. The performance data given is based on results achieved during tests conducted under ideal test conditions in a laboratory. Actual site conditions may result in variation in these performance values. Depending upon customer feedback and continual improvement, new models are introduced on regular basis, kindly consult your local dealer/re-seller for appropriate pump selection.

Total Head=Suction Head + Delivery Head + Friction Los ses