















Delivery Size : 80/100 mm (3/4")				KRM – 30 : MIXED FLOW				Maximum Outer Diameter : 196 mm						
Pump Model	Motor Rating kW/HP	Stages	Conn. (Starter)	LPS	0	4.0	8.0	10.0	13.0	17.0	19.5	23.5	Max. Current (A)	ISI Mark
				LPM	0	240	480	600	780	1020	1170	1410		
				LPH	0	14400	28800	36000	46800	61200	70200	84600		
KRM-30/10/3	7.5/10.0	3	S/D	Head in Mtrs.	51	48	45	43	39	35	30	27	21.2	
KRM-30/12.5/4	9.3/12.5	4	S/D		68	64	60	57	52	47	40	36	27.3	
KRM-30/15/5	11.0/15.0	5	S/D		85	80	75	72	65	58	50	45	31.6	
KRM-30/17.5/6	13.0/17.5	6	S/D		102	96	90	86	78	70	60	54	37.1	
KRM-30/20/7	15.0/20.0	7	S/D		119	112	105	100	91	82	70	63	42.6	
KRM-30/25/8	18.5/25.0	8	S/D		136	128	120	115	104	93	80	72	51.9	
KRM-30/30/10	22.0/30.0	10	S/D		170	160	150	143	130	117	100	90	62.2	



Delivery Size : 80/100 mm (3/4")				KRM – 40 : MIXED FLOW				Maximum Outer Diameter : 196 mm						
Pump Model	Motor Rating kW/HP	Stages	Conn. (Starter)	LPS	0	5.0	9.5	12.0	16.0	19.0	23.0	25.0	Max. Current (A)	ISI Mark
				LPM	0	300	570	720	960	1140	1380	1500		
				LPH	0	18000	34200	43200	57600	68400	82800	90000		
KRM-40/12.5/3	9.3/12.5	3	S/D	Head in Mtrs.	60	54	50	46	42	37	32	27	27.3	
KRM-40/15/4	11.0/15.0	4	S/D		80	72	67	61	56	49	43	36	31.6	
KRM-40/20/5	15.0/20.0	5	S/D		100	90	83	77	70	62	53	45	42.6	
KRM-40/25/6	18.5/25.0	6	S/D		120	108	100	92	84	74	64	54	51.9	
KRM-40/30/7	22.0/30.0	7	S/D		140	126	117	107	100	86	75	63	62.2	
KRM-40/35/9	26.0/35.0	9	S/D		180	162	150	138	126	111	96	81	70.7	
KRM-40/40/10	30.0/40.0	10	S/D		200	180	167	153	140	123	107	90	80.8	




Delivery Size : 100 mm (4")				KRM – 50 : MIXED FLOW				Maximum Outer Diameter : 196 mm						
Pump Model	Motor Rating kW/HP	Stages	Conn. (Starter)	LPS	0	7.0	11.5	17.5	20.5	24.0	27.0	28.5	Max. Current (A)	ISI Mark
				LPM	0	420	690	1050	1230	1440	1620	1710		
				LPH	0	25200	41400	63000	73800	86400	97200	102600		
KRM-50/10/2	7.5/10.0	2	S/D	Head in Mtrs.	45	40	37	33	30	26	22	19	21.2	
KRM-50/15/3	11.0/15.0	3	S/D		68	60	56	50	45	39	33	29	31.6	
KRM-50/20/4	15.0/20.0	4	S/D		90	80	74	66	60	52	44	38	42.6	
KRM-50/25/5	18.5/25.0	5	S/D		113	100	93	83	75	65	55	48	51.9	
KRM-50/30/6	22.0/30.0	6	S/D		135	120	111	99	90	78	66	57	62.2	
KRM-50/35/7	26.0/35.0	7	S/D		158	140	130	116	105	91	77	67	70.7	
KRM-50/40/8	30.0/40.0	8	S/D		180	160	148	132	120	104	88	76	80.8	
KRM-50/45/9	33.0/45.0	9	S/D		203	180	167	149	135	117	99	86	88.5	
KRM-50/50/10	37.5/50.0	10	S/D		225	200	185	165	150	130	110	95	100.3	

Statutory Disclaimer:- In view of continual development, the performance figures / information / description / illustrations are subject to change without any prior notice. The performance data given is based on results achieved during tests conducted under ideal test conditions in a laboratory. Actual site conditions may result in variation in these performance values. Depending upon customer feedback and continual improvement, new models are introduced on regular basis, kindly consult your local dealer/re-seller for appropriate pump selection.

Total Head=Suction Head+ Delivery Head+ Friction Losses


Delivery Size : 100 mm (4")				KRM – 60 : MIXED FLOW				Maximum Outer Diameter : 196 mm						
Pump Model	Motor Rating kW/HP	Stages	Conn. (Starter)	LPS	0	10.0	15.0	21.0	24.5	26.5	28.0	30.0	Max. Current (A)	ISI Mark
				LPM	0	600	900	1260	1470	1590	1680	1800		
				LPH	0	36000	54000	75600	88200	95400	100800	108000		
KRM-60/12.5/2	9.3/12.5	2	S/D	Head in Mtrs.	46	40	37	33	30	26	22	19	27.3	
KRM-60/17.5/3	13.0/17.5	3	S/D		69	60	56	50	45	39	33	29	37.1	
KRM-60/25/4	18.5/25.0	4	S/D		92	80	74	66	60	52	44	38	51.9	
KRM-60/30/5	22.0/30.0	5	S/D		115	100	93	83	75	65	55	48	62.2	
KRM-60/35/6	26.0/35.0	6	S/D		138	120	111	99	90	78	66	57	70.7	
KRM-60/40/7	30.0/40.0	7	S/D		161	140	130	116	105	91	77	67	80.8	
KRM-60/50/8	37.5/50.0	8	ATS		184	160	148	132	120	104	88	76	100.3	

Delivery Size : 100 mm (4")				KRM – 70 : MIXED FLOW				Maximum Outer Diameter : 196 mm						
Pump Model	Motor Rating kW/HP	Stages	Conn. (Starter)	LPS	0	10.5	16.0	22.5	26.0	29.0	31.0	32.5	Max. Current (A)	ISI Mark
				LPM	0	630	960	1350	1560	1740	1860	1950		
				LPH	0	37800	57600	81000	93600	104400	111600	117000		
KRM-70/15/2	11.0/15.0	2	S/D	Head in Mtrs.	47	42	38	34	30	26	22	19	31.6	
KRM-70/20/3	15.0/20.0	3	S/D		71	63	57	51	45	39	33	29	42.6	
KRM-70/30/4	22.0/30.0	4	S/D		94	84	76	68	60	52	44	38	62.2	
KRM-70/35/5	26.0/35.0	5	S/D		118	105	95	85	75	65	55	48	70.7	
KRM-70/40/6	30.0/40.0	6	S/D		141	126	114	102	90	78	66	57	80.8	
KRM-70/50/7	37.5/50.0	7	TAS		165	147	133	119	105	91	77	67	100.3	
KRM-70/55/8	41.2/55.0	8	ATS		188	168	152	136	120	104	88	76	108.1	
KRM-70/60/9	45.0/60.0	9	ATS	212	189	171	153	135	117	99	86	118.0		

Delivery Size : 100 mm (4")				KRM – 80 : MIXED FLOW				Maximum Outer Diameter : 196 mm						
Pump Model	Motor Rating kW/HP	Stages	Conn. (Starter)	LPS	0	11.0	17.0	24.0	28.0	32.0	34.0	35.0	Max. Current (A)	ISI Mark
				LPM	0	660	1020	1440	1680	1920	2040	2100		
				LPH	0	39600	61200	86400	100800	115200	122400	126000		
KRM-80/15/2	11.0/15.0	2	S/D	Head in Mtrs.	48	43	40	36	32	28	24	20	31.6	
KRM-80/25/3	18.5/25.0	3	S/D		72	65	60	54	48	42	36	30	51.9	
KRM-80/30/4	22.0/30.0	4	S/D		96	86	80	72	64	56	48	40	62.2	
KRM-80/40/5	30.0/40.0	5	S/D		120	108	100	90	80	70	60	50	80.8	
KRM-80/50/6	37.5/50.0	6	ATS		144	129	120	108	96	84	72	60	100.3	
KRM-80/55/7	41.2/55.0	7	ATS		168	151	140	126	112	100	84	70	108.1	

Statutory Disclaimer:- In view of continual development, the performance figures / information / description / illustrations are subject to change without any prior notice. The performance data given is based on results achieved during tests conducted under ideal test conditions in a laboratory. Actual site conditions may result in variation in these performance values. Depending upon customer feedback and continual improvement, new models are introduced on regular basis, kindly consult your local dealer/re-seller for appropriate pump selection.

Total Head=Suction Head+ Delivery Head+ Friction Losses

Delivery Size : 100/125 mm (4/5")				KRM – 90 : MIXED FLOW				Maximum Outer Diameter : 196 mm						
Pump Model	Motor Rating kW/HP	Stages	Conn. (Starter)	LPS	0	13.0	20.5	26.0	30.0	33.0	35.5	37.5	Max. Current (A)	ISI Mark
				LPM	0	780	1230	1560	1800	1980	2130	2250		
				LPH	0	46800	73800	93600	108000	118800	127800	135000		
KRM-90/17.5/2	13.0/17.5	2	S/D	Head in Mtrs.	48	44	40	36	32	28	24	20	37.1	
KRM-90/30/3	22.0/30.0	3	S/D		72	66	60	54	48	42	36	30	62.2	
KRM-90/35/4	26.0/35.0	4	S/D		96	88	80	72	64	56	48	40	70.7	
KRM-90/45/5	33.5/45.0	5	S/D		120	110	100	90	80	70	60	50	88.5	
KRM-90/55/6	41.2/55.0	6	ATS		144	132	120	108	96	84	72	60	108.1	
KRM-90/60/7	45.0/60.0	7	ATS		168	154	140	126	112	100	84	70	118.0	

Delivery Size : 100/125 mm (4/5")				KRM – 100 : MIXED FLOW				Maximum Outer Diameter : 196 mm						
Pump Model	Motor Rating kW/HP	Stages	Conn. (Starter)	LPS	0	15.0	24.0	29.0	34.5	37.5	39.0	41.0	Max. Current (A)	ISI Mark
				LPM	0	900	1440	1740	2070	2250	2340	2460		
				LPH	0	54000	86400	104400	124200	135000	140400	147600		
KRM-100/10/1	7.5/10.0	1	S/D	Head in Mtrs.	24	22	20	18	16	14	12	10	21.2	
KRM-100/20/2	15.0/20.0	2	S/D		48	44	40	36	32	28	24	20	42.6	
KRM-100/30/3	22.0/30.0	3	S/D		72	66	60	54	48	42	36	30	62.2	
KRM-100/40/4	30.0/40.0	4	S/D		96	88	80	72	64	56	48	40	80.8	
KRM-100/50/5	37.5/50.0	5	ATS		120	110	100	90	80	70	60	50	100.3	
KRM-100/60/6	45.0/60.0	6	ATS		144	132	120	108	96	84	72	60	118.0	

Statutory Disclaimer:- In view of continual development, the performance figures / information / description / illustrations are subject to change without any prior notice. The performance data given is based on results achieved during tests conducted under ideal test conditions in a laboratory. Actual site conditions may result in variation in these performance values. Depending upon customer feedback and continual improvement, new models are introduced on regular basis, kindly consult your local dealer/re-seller for appropriate pump selection.

Total Head=Suction Head + Delivery Head + Friction Losses

Delivery Size : 125 mm (5")				KRM – 120 : MIXED FLOW				Maximum Outer Diameter : 210 mm						
Pump Model	Motor Rating kW/HP	Stages	Conn. (Starter)	LPS	0	19.0	26.0	34.0	40.0	45.0	50.0	55.0	Max. Current (A)	ISI Mark
				LPM	0	1140	1560	2040	2400	2700	3000	3300		
				LPH	0	68400	93600	122400	144000	162000	180000	1100000		
KRM-120/12.5/1	9.3/12.5	1	S/D	Head in Mtrs.	27	23	21	19	17	15	13	11	27.3	
KRM-120/25/2	18.5/25.0	2	S/D		54	46	42	38	34	30	26	22	51.9	
KRM-120/35/3	26.0/35.0	3	S/D		81	69	63	57	51	45	39	33	70.7	
KRM-120/50/4	37.5/50.0	4	ATS		108	92	84	76	68	60	52	44	100.3	
KRM-120/60/5	45.0/60.0	5	ATS		135	115	105	95	85	75	65	55	118.0	

Delivery Size : 125 mm (5")				KRM – 150 : MIXED FLOW				Maximum Outer Diameter : 210 mm						
Pump Model	Motor Rating kW/HP	Stages	Conn. (Starter)	LPS	0	23.5	29.0	41.0	47.0	52.0	56.0	60.0	Max. Current (A)	ISI Mark
				LPM	0	1410	1740	2460	2820	3120	3360	3600		
				LPH	0	84600	104400	147600	169200	187200	201600	216000		
KRM-150/15/1	11.0/15.0	1	S/D	Head in Mtrs.	28	24	22	20	18	15	13	11	31.6	
KRM-150/30/2	22.0/30.0	2	S/D		56	48	44	39	35	30	26	22	62.2	
KRM-150/45/3	33.5/45.0	3	S/D		84	72	66	59	53	45	39	33	88.5	
KRM-150/60/4	45.0/60.0	4	ATS		112	96	88	78	70	60	52	44	118.0	

Statutory Disclaimer:- In view of continual development, the performance figures / information / description / illustrations are subject to change without any prior notice. The performance data given is based on results achieved during tests conducted under ideal test conditions in a laboratory. Actual site conditions may result in variation in these performance values. Depending upon customer feedback and continual improvement, new models are introduced on regular basis, kindly consult your local dealer/re-seller for appropriate pump selection.

Total Head=Suction Head + Delivery Head + Friction Losses